

COLD Water: Electric Powered – Stationary or Portable

The **CN Series** offers auto on/off with adjustable time delay shutdown and a unique design for versatile mounting and portability. The auto on/off feature allows you to clean with just one squeeze of the spray gun, no traveling back and forth to the unit to adjust the pressure. Designed with durable heavy-duty components for a lifetime of performance and constructed of stainless steel for corrosion resistance. Whether used stationary or with the optional wheel kit, this cold water unit delivers high-pressure cleaning for any work where electric power is available.

PRESSURE	3500 PSI
FLOW CAPACITY	4.3 GPM
POWER/ENGINE	10 hp
VOLTS / PHASE / AMPS	E3 is dual rated for 208 or 230v - 3ph / 27amp E4 is 460v / 3ph / 14amp
CONTROLS/SWITCHES	Hour meter, lighted on/off switch, panel mounted soap control
POWER DRIVE	V-Belt Drive, Low RPM – cooler, quieter, continuous duty performance
PUMP	Cat Pump, oil bath, Triplex, ceramic plunger, brass head, stainless steel valves
PRESSURE CONTROL	Adjustable Unloader, adjustable pressure wand, Safety Relief Valve
WATER SUPPLY	Pressure Feed From Garden Hose, 3½ gal. Float Tank With 50 Mesh Filter
PRESSURE HOSE	3/8" x 50' 4000psi Steel Wire Braid Hose
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler
SOAP INJECTION	Inlet Soap/Chemical Injection at Full Pressure, Stainless Steel Chemical Metering Valve
NOZZLE	#4.5 (15°,25°,40°)
FRAME CONSTRUCTION	Stainless Steel frame, panels and removable cover
WHEELS	Optional wheel/handle kit available
DIMENSIONS (LxWxH)	31" x 21" x 14" (Dim with wheel kit: 39" x 29 ½" x 36")
NET WEIGHT	193#

*Specifications subject to change without notification and may vary due to ambient conditions



Featuring:

- ✓ **Removable cover** for easy access and serviceability
- ✓ **Cat V-belt driven pump** for long lasting performance
- ✓ **NEMA Water Tight** electrical control box provides protection and easy access.
- ✓ **Full pressure** soap injection for better cleaning
- ✓ **Auto ON/Off** with time delay shutdown saves time & money.

Options...

Multi station outlets (ACW20), wall mount bracket (ACW09), wet sandblaster, wall mount hose reels (AR188-5000psi), wheel/handle kit (AHS15), 24 volt remote start/stop with 50' cord (AEN35), 24 volt remote start/stop with soap control (AEN22)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____



CN Series and CW Series both pictured.
(CN shown w/optional wheel kit)