

### Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The **HD Series** offers rugged, dependable, affordable washing. It features a heavy-duty stainless steel frame, handles, panels and coil protection – offering superior corrosion resistance, as well as four pneumatic wheels. Panel mounted temperature control offers the benefits of high pressure cleaning with water temperature from cold through full Steam Settings. Panel mounted controls allow the operator to vary the mixture of soap, or other additives, which can be delivered at full pressure – for optimal cleaning effectiveness. High efficiency dual pass coil and large capacity diesel fuel tank offer up to 8 hours of operation between refueling. Ideal for farm and agricultural applications, auto repair shops, and wherever sanitizing and degreasing are needed.

<b>PRESSURE</b>	2500psi
<b>FLOW CAPACITY</b>	3.6gpm
<b>OUTLET TEMP</b>	Adj. to 250°F (140°F Rise)
<b>POWER/ENGINE</b>	6.5 HP
<b>VOLTS/PHASE/AMPS</b>	230v / 1ph / 27a
<b>POWER CORD</b>	35' cord with Ground Fault Circuit Interrupter for additional safety
<b>CONTROLS/SWITCHES</b>	Lighted rocker switches, panel mounted soap control, adjustable thermostat
<b>PUMP</b>	Cat Pump, Triplex ceramic plunger w/oil bath, brass head, stainless steel valves
<b>POWER DRIVE</b>	V-Belt Drive, Low RPM – Cooler, Quieter, Continuous Duty Performance
<b>PRESSURE CONTROL</b>	Adjustable Pressure Unloader, Safety Relief Valve, Burst Disc, By-Pass-Cool System
<b>WATER SUPPLY</b>	4 Gal Float Tank, Double Inlet Filtration, Back Flow Prevention
<b>PRESSURE HOSE</b>	3/8" x 50' Steel Wire Braid Hose, 3000 PSI, 250°F Rated
<b>GUN / WAND</b>	Insulated Shut Off Gun / 36" Wand w/Nozzle Quick Connector
<b>SOAP INJECTION</b>	Inlet soap/chemical injection, Injects Soap At Full Pressure
<b>NOZZLE</b>	#4.5(0°,15°) #3.5(25°)
<b>BURNER COIL</b>	1/2" Sch 80 Coil, Stainless Steel Coil Enclosure, Dual Pass, High Efficiency
<b>BURNER/POWER</b>	Beckett Oil Fired, Automatic Ignition, Forced Draft, Fuel Filter w/ Water Separator
<b>BURNER FUEL / CAP</b>	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gal. capacity, up to 8hrs. run time
<b>FRAME CONSTRUCTION</b>	Stainless steel frame, coil wrap and panels
<b>WHEELS</b>	4) 10" foam filled wheels installed
<b>NET WEIGHT / DIMS</b>	378# 47x29x36

\*Specifications subject to change without notification and may vary due to ambient conditions.

### Featuring:

- ✓ **High Efficiency Heater** – Unique Dual Pass coil, with double wall stainless steel insulation, capture heat on both sides of the Schedule 80 pipe to burn less fuel.
- ✓ **Flexible, Effective Cleaning:** Adjustable temperature with steam setting and soap/chemical injection delivers more cleaning power over a wide range of applications.
- ✓ **Compact and Portable** – Wheels included. Easily moved to wherever you need to clean

### Options...

Stainless Steel Hose Reel (AR003)



TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_