

Steam / Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine, 12v Burner

The **SS Series** is a power washer that uses the 12-volt charging system on the engine to power the diesel-fired burner giving you continuous hot water. Its compact size allows passage through standard doorways, and simple design makes it easy to run and maintain. The SS series is versatile, you select a mounting option: on a trailer, on a truck, on wheels or stationary. The SS Series has the output to perform heavy duty cleaning without needing any outside electrical power. Simply turn the key for high pressure, hot cleaning strength. An invaluable piece of equipment for property management companies, farmers, mechanics or anyone requiring a mobile cleaning solution for dirt, grease, and grime.

PRESSURE	4000 psi
FLOW CAPACITY	4 gpm
OUTLET TEMP	Adjustable Thermostat to 250°F; 140°F Heat Rise
POWER/ENGINE	16hp Vanguard, Twin-Cylinder, Electric Start
ENGINE FUEL/CAP	Unleaded, 8 gal
CONTROLS/SWITCHES	Adjustable thermostat, lighted control switch
PUMP	AR Pump, Triplex Ceramic Plunger
POWER DRIVE	V Belt Drive
PRESSURE CONTROL	Unloader Valve, Industrial Fittings, Safety Burst Disc
WATER SUPPLY	Pressure feed from garden hose (no float tank), convenient frame mounted inlet fitting
PRESSURE HOSE	3/8" x 50', 4000psi
GUN/WAND	48" molded insulator wand with multi-nozzle holder and quick coupler
SOAP INJECTION	Optional soap injection available
NOZZLE	Size 4.0 (0°, 15°) and 3 (25° steam)
BURNER COIL	1/2" sch. 80 coil, 4 pancake, ceramic blanket insulation
BURNER/POWER	Oil fired, 12V, 20amp fuse protected, auto ignition, in-line fuel filter, flow switch burner control
BURNER FUEL/CAP	Diesel fuel, kerosene, or fuel oil, 8 gallons
CONSTRUCTION	Heavy gauge steel, powder coated, Pro-Tec-It frame, Stainless panels and coil wrap
WHEELS	Optional wheel kit available
WEIGHT/DIMENSION	448#, 45x23x40

Specifications subject to change without notification and may vary due to ambient conditions



Featuring:

- ✓ **Rugged "Pro-Tec-It" Frame** can be truck or trailer mounted or rolled through a 30" doorway with the optional wheel kit.
- ✓ **Stainless Steel** panels for Lifetime Corrosion Resistance
- ✓ **Commercial / Industrial engines** with high output charging circuit
- ✓ **Flow Controlled Burner** for low & high Pressure Steam for thawing
- ✓ **High Output Burner** with 150° to 175° F heat rise for cold water input

Options...

Hose Reel (AR188), Hour meter (AM305), Wheel Kit options (AHA12, AHB12, or AHS12), Downstream soap injection kit (AC340), Float tank with inlet injection (WT0SS), Antifreeze tank (WT0SW), Mobile Wash Trailer, Tank Skid

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

