

**ProTowWash® – Transport Trailer with 400 Gallon Tank**

The T400 tandem axle trailer, with your choice of pressure washer, is a fully integrated self-contained pressure washing system. The two 200 Gallon water tanks with integrated baffling provide 400 Gallons of ample water to sustain many remote-cleaning requirements. The dual water tanks provide flexibility for operation and can be either plumbed together or maintained separate. The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum.

TECHNICAL DATA	T400EE	T400S
MACHINE CAPACITY	SS, SC, SCU Series (up to 1100# Total)	
SUSPENSION / AXLE	Two 3700# Torsion Axles-Up to 300% more wheel travel over conventional trailer	
TRAILER BRAKES	Electric brakes both axles, breakaway switch***	Surge Brake – Rear Axle
WHEEL / TIRE	4 - 14" White Spoke Rims, 5 Lug, ST205/75d 14 Tires, 1760 Pounds capacity per tire	
COUPLER / TONGUE	2" Ball Coupler, Dual 5/16" Safety Chains	
VEHICLE HITCH / GVWR	2" Ball Hitch, Class III 5000 Pound Rated, 21" to top of ball when trailer is attached 5000# GVWR	
FENDERS	12 GA Steel Fender with recessed tail light mount	
LIGHTS	Recessed Rubber Grommet Snap-In, DOT Approved	
WIRING	7 way molded electrical connector	4 way flat electrical connector
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter	
WATER TANK	400 gal. total capacity (dual 200 gal) polyethylene, 10" lid, garden hose fill fitting	
TANK DRAW / FILTER	1½" 80 Mesh Strainer with Drain, 1½" Fast Drain Valve	
CHASSIS CONST.	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish	
WEIGHT/DIMENSIONS	985# Empty (No Machine) 156"L x 70"W x 61"H	

Note: Specifications subject to change without notification and may vary due to ambient conditions.

Note: Shipped to distributors only – Not available to drop ship – Assembly Required

\*\*\* Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery.

**Featuring:**

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated storage tube for spray wands and large (47"x22"x10") storage box at the back of trailer for hoses and other accessories.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitations & contamination

**Options...**

Hose Reels, Lunette eye hitch, Custom trailer color (CTRLR), Chrome wheel upgrade, Front Bucket Rack (ACR02), 3-way ball valve (AW006), Pump seal saver bypass (APS50)-installed, Low water shutdown (AW410)-installed, Sand hopper, Light Bar rack (HLB98), Vacuum hose hooks (HHP28), Hydro Vacuum wastewater recycle (AZV), 12v chemical sprayer with 40gal tank (AC440), Locking storage lid option (ATH50)



Pressure washer not included  
 Shown with optional Hose Reel, Light Bar, and front bucket rack

**TO:** \_\_\_\_\_

**COMMENTS:** \_\_\_\_\_

**YOUR PRICE:** \_\_\_\_\_

**DISTRIBUTED BY:** \_\_\_\_\_

**WARNING:** Trailer brakes and a breakaway switch are recommended and required on the road in most states if the trailer weight exceeds 1500 pounds gross. Check your states requirements.