

# HYDRO TEK

CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374  
 phone 800.274.9376 or 1.909.799.9222  
 www.hydrotek.us fax 909.799.9888

# SC30009KAF

## SC Series – Mobile Wash Skid 2 Gun, adjustable flow

### Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine

The **SC Series – 2 Gun** offers the most versatile hot water pressure washers on the market today. Each skid comes equipped to allow the operator to vary the flow of the machine and reliably handle a two-gun set-up. The system is uniquely engineered to balance 1 or 2 gun operations. The SC Series is powered by industrial engines, hi torque–low RPM belt driven pumps and reliable 110v burner system with a 2.9Kw generator, providing power for running a water recycling system or other accessories. If portability is needed add a wheel kit or mount on a trailer, truck bed or tank skid.

|                          |                                                                                                                                               |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRESSURE</b>          | 3000psi (207 bar)                                                                                                                             |
| <b>FLOW CAPACITY</b>     | 8.5 gpm (two operators, 4.25 gpm ea.)                                                                                                         |
| <b>OUTLET TEMP</b>       | Adjustable to 200°F (100°F rise)                                                                                                              |
| <b>POWER/ENGINE</b>      | 725cc Kohler                                                                                                                                  |
| <b>ENGINE FUEL/CAP</b>   | Unleaded gasoline, 8 Gal.- 6 hrs run time                                                                                                     |
| <b>CONTROLS/SWITCHES</b> | Adjustable thermostat, lighted burner control switch, optional hour meter available                                                           |
| <b>PUMP</b>              | General Pump                                                                                                                                  |
| <b>POWER DRIVE</b>       | V-Belt Drive with EZ Align™ pump rail, stainless belt guard                                                                                   |
| <b>PRES. CONTROL</b>     | Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve                                                   |
| <b>WATER SUPPLY</b>      | Minimum 25 gallon bulk supply tank required                                                                                                   |
| <b>PRESSURE HOSE</b>     | Qty 2 - 3/8" x 50', 3000psi 250° rated                                                                                                        |
| <b>GUN / WAND</b>        | Qty 2 - 48" molded insulator wand with multi-nozzle holder and quick coupler                                                                  |
| <b>SOAP INJECTION</b>    | Optional soap injection available                                                                                                             |
| <b>NOZZLE</b>            | #10, #9, #8, & 2qty) #5.5 (15°)                                                                                                               |
| <b>BURNER COIL</b>       | Spiralast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 6 spiral, ceramic insulation                                                |
| <b>BURNER/POWER</b>      | Oil Fired, 115 volt, Auto Ignition, Spin-on fuel filter                                                                                       |
| <b>BURNER FUEL/CAP</b>   | Diesel #1 or #2, Kerosene, 18 gal. – 550,000 Btu input                                                                                        |
| <b>GENERATOR</b>         | On-board 2900 watt, 115v, brushless, generator                                                                                                |
| <b>CONSTRUCTION</b>      | Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) |
| <b>WHEELS</b>            | Optional wheel kit available                                                                                                                  |
| <b>NET WEIGHT/DIM.</b>   | 729# 51"x34"x39"                                                                                                                              |

\*Specifications subject to change without notification and may vary due to ambient conditions – Battery not included

#### Featuring:

- ✓ **Rugged "Protect-It" Frame**, with 4-point lifting or tie down eyes and hose reel mounting points, can be truck or trailer mounted or pulled/towed with the optional wheel kit
- ✓ **Super Duty Burner System** uses schedule 80 coil pipe, stainless steel and ceramic insulation combined with a proven 110 volt oil fired burner for trouble free and efficient heating
- ✓ **Adjustable Flow System** can be used for 2-gun operation or to reduce water flow, conserving water, when using one gun

#### Options...

Stainless frame option (HS208), Custom skid color (CTSKD), Trailer, Tank Skid, Wheel Kit 13" w/pull bar steering (AHB12), locking kit for wheel kit (AHB20), Hose Reel (AR425, AR100, AR150), Winterizing tank (AWTW5), Downstream injection (AC360 or AC380), Float Tank w/inlet injection (WT056), Hour meter (AM601), Hydro Vacuum wastewater recovery



TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_