

SC35006DAF

SC Series – Mobile Wash Skid Adjustable flow

Hot / Cold Water - Self Contained: Diesel Heated, Diesel Engine

The *SC Series, AF models* offer the most versatile hot water pressure washers on the market today. Each skid allows the operator to vary the flow of the machine and reliably handle a two-gun set-up. The system is engineered to uniquely balance 1 or 2 gun operations. The SC Series is powered by industrial engines, hi torque–low RPM belt driven pumps and reliable 110v burner system with a 2.9Kw generator, providing power for running a water recycling system or other accessories. If portability is needed add a wheel kit or mount on a trailer, truck bed or tank skid. Simply add the second

gun/hose kit (part# AVG53) if needed for second operator.

PRESSURE FLOW CAPACITY OUTLET TEMP Adjustable to 200°F (100°F rise) POWER/ENGINE ENGINE FUEL/CAP ENGINE FUEL/CAP Adjustable thermostat, lighted burner and engine CONTROLS/SWITCHES PUMP General Pump POWER DRIVE V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails PRES. CONTROL Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve WATER SUPPLY Minimum 25 gallon bulk supply tank required PRESSURE HOSE 3/8" x 50", 4000psi 250° rated 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) NET WEIGHT/DIM. 649# 51"x34"x39"	guil/110se kii (pari# Av 655)	il needed for second operator.		
OUTLET TEMP Adjustable to 200°F (100°F rise) POWER/ENGINE ENGINE FUEL/CAP #2 Diesel, 18 gallon for burner and engine CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, hour meter PUMP General Pump POWER DRIVE V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails PRES. CONTROL Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve WATER SUPPLY Minimum 25 gallon bulk supply tank required PRESSURE HOSE 3/8" x 50', 4000psi 250° rated 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	PRESSURE	3500psi (241 bar)		
POWER/ENGINE ENGINE FUEL/CAP #2 Diesel, 18 gallon for burner and engine CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, hour meter PUMP General Pump V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails PRES. CONTROL Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve WATER SUPPLY Minimum 25 gallon bulk supply tank required PRESSURE HOSE 3/8" x 50', 4000psi 250° rated 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine On-board 2900 watt, 115v, brushless, generator Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	FLOW CAPACITY	5.5gpm		
#2 Diesel, 18 gallon for burner and engine CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, hour meter PUMP General Pump POWER DRIVE V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails PRES. CONTROL Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve WATER SUPPLY Minimum 25 gallon bulk supply tank required PRESSURE HOSE 3/8" x 50', 4000psi 250° rated GUN / WAND 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	OUTLET TEMP	Adjustable to 200°F (100°F rise)		
CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, hour meter PUMP General Pump POWER DRIVE V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails PRES. CONTROL Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve WATER SUPPLY Minimum 25 gallon bulk supply tank required PRESSURE HOSE 3/8" x 50', 4000psi 250° rated GUN / WAND 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine – 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	POWER/ENGINE	599cc Kubota		
PUMP POWER DRIVE V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails PRES. CONTROL Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve WATER SUPPLY Minimum 25 gallon bulk supply tank required PRESSURE HOSE 3/8" x 50', 4000psi 250° rated GUN / WAND 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	ENGINE FUEL/CAP	#2 Diesel, 18 gallon for burner and engine		
POWER DRIVE PRES. CONTROL Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve WATER SUPPLY Minimum 25 gallon bulk supply tank required PRESSURE HOSE 3/8" x 50', 4000psi 250° rated GUN / WAND 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	CONTROLS/SWITCHES	Adjustable thermostat, lighted burner control switch, hour meter		
PRES. CONTROL Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve WATER SUPPLY Minimum 25 gallon bulk supply tank required PRESSURE HOSE 3/8" x 50', 4000psi 250° rated GUN / WAND 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine – 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	PUMP	General Pump		
WATER SUPPLYMinimum 25 gallon bulk supply tank requiredPRESSURE HOSE3/8" x 50', 4000psi 250° ratedGUN / WAND48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available)SOAP INJECTIONOptional downstream injection availableNOZZLE#5.5, #5, #4 & #2.7 (15°)BURNER COILSpiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulationBURNER/POWEROil Fired, 115 volt, Auto Ignition, Spin-on Fuel FilterBURNER FUEL/CAPDiesel #2, 18 gallon for burner and engine − 514.000 Btu inputGENERATOROn-board 2900 watt, 115v, brushless, generatorCONSTRUCTIONRugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available)WHEELSOptional wheel kit available	POWER DRIVE	V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance. Easy Tension Rails		
PRESSURE HOSE GUN / WAND 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	PRES. CONTROL	Adjustable pressure unloader, Industrial fittings, Safety burst disc, Pressure relief valve		
GUN / WAND 48" molded insulator wand with multi-nozzle holder and quick coupler (second gun/hose kit available) SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	WATER SUPPLY	Minimum 25 gallon bulk supply tank required		
(second gun/hose kit available) SOAP INJECTION Optional downstream injection available #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	PRESSURE HOSE	3/8" x 50', 4000psi 250° rated		
SOAP INJECTION Optional downstream injection available NOZZLE #5.5, #5, #4 & #2.7 (15°) BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available				
NOZZLE#5.5, #5, #4 & #2.7 (15°)BURNER COILSpiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulationBURNER/POWEROil Fired, 115 volt, Auto Ignition, Spin-on Fuel FilterBURNER FUEL/CAPDiesel #2, 18 gallon for burner and engine − 514.000 Btu inputGENERATOROn-board 2900 watt, 115v, brushless, generatorCONSTRUCTIONRugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available)WHEELSOptional wheel kit available				
BURNER COIL BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	SOAP INJECTION	Optional downstream injection available		
BURNER/POWER Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	NOZZLE	#5.5, #5, #4 & #2.7 (15°)		
BURNER FUEL/CAP Diesel #2, 18 gallon for burner and engine − 514.000 Btu input GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	BURNER COIL	Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation		
GENERATOR On-board 2900 watt, 115v, brushless, generator CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	BURNER/POWER	Oil Fired, 115 volt, Auto Ignition, Spin-on Fuel Filter		
CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	BURNER FUEL/CAP	Diesel #2, 18 gallon for burner and engine – 514.000 Btu input		
coil end caps (stainless steel frame option available) WHEELS Optional wheel kit available	GENERATOR	On-board 2900 watt, 115v, brushless, generator		
WHEELS Optional wheel kit available	CONSTRUCTION			
NET WEIGHT/DIM. 649# 51"x34"x39"	WHEELS	Optional wheel kit available		
	NET WEIGHT/DIM.	649# 51"x34"x39"		

^{*}Specifications subject to change without notification and may vary due to ambient conditions – Battery not included

Featuring:

- Rugged Pro-Tect-It frame can be truck or trailer mounted or pulled/towed with the optional wheel kit
- ✓ **Super Duty Burner System** uses schedule 80 coil pipe, stainless steel and ceramic insulation combined with a proven 110 volt oil fired burner for trouble free and efficient heating
- ✓ Adjustable Flow System can be used for 2-gun operation or to reduce water flow, conserving water, when using one gun

Options...

Second gun/hose (AVG53), Stainless frame option with 4-point lifting sling (HS215), Custom skid color (CTSKD), Winterizing tank (AWTW5), Down Stream Injection (AC380 or AC360), Trailer, Tank Skid, Wheel Kit 13" w/pull bar steering (AHB12), locking kit for wheel kit (AHB20), Hose Reel (AR425), Hydro Vacuum wastewater recovery

TO:	 	
COMMENTS:	 	
YOUR PRICE:		
DISTRIBUTED BY:		



