

# SS35003VH

## SS Series - Mobile Wash Skid

## Steam / Hot / Cold Water - Self Contained: Diesel Heated, Gas Engine, 12v Burner

The **SS Series** is a power washer that uses the 12-volt charging system on the engine to power the diesel-fired burner giving you continuous hot water. Its compact size allows passage through commercial doorways, and simple design makes it easy to run and maintain. The SS series is versatile, you select a mounting option: on a trailer, on a truck, on wheels or stationary. The SS Series has the output to perform heavy duty cleaning without needing any outside electrical power. Simply turn the key for high pressure, hot cleaning strength. An invaluable piece of equipment for property management companies, farmers, mechanics or anyone requiring a mobile cleaning solution for dirt, grease, and grime.

| PRESSURE          | 3500psi   |
|-------------------|---|
| FLOW CAPACITY     | 3.5gpm  |
| OUTLET TEMP       | Adjustable to 250°F (130°F rise)  |
| POWER/ENGINE      | 479cc Vanguard, twin cylinder – electric key start  |
| ENGINE FUEL/CAP   | Unleaded, 8 gal   |
| CONTROLS/SWITCHES | Adjustable thermostat, lighted control switch   |
| PUMP              | AR Pump   |
| POWER DRIVE       | Direct Drive  |
| PRESSURE CONTROL  | Unloader valve, Industrial fittings, Safety burst disc, relief valve                              |
| WATER SUPPLY      | Pressure feed from garden hose with convenient frame mounted fitting                              |
| PRESSURE HOSE     | 3/8" x 50', 4000psi   |
| GUN/WAND          | 48" molded insulator wand with quick coupler  |
| SOAP INJECTION    | Downstream soap injection option available  |
| NOZZLE            | Size 3.5 (15°, 40°), size 3.0 (25° steam)   |
| BURNER COIL       | Spiralast™ robotically fused ½" sch. 80 steel, cold rolled, compact, 4 spiral, ceramic insulation |
| BURNER/POWER      | Oil fired, 12V, 20amp fuse protected, auto ignition, inline fuel filter                           |
| BURNER FUEL/CAP   | Diesel fuel, kerosene, or fuel oil, 8 gallons – 299,600 Btu input                                 |
| CONSTRUCTION      | Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil       |
|                   | end caps  |
| WHEELS            | Optional wheel kit available  |
| WEIGHT/DIMENSION  | 439#, 47½" l x 27.5" w x 40.25" h   |
|                   |   |

Specifications subject to change without notification and may vary due to ambient conditions - Battery not included

### Featuring:

- Rugged "Pro-Tec-It" Frame surrounds and protects vital pressure washer components.
- ✓ **Stainless Steel** panels for Lifetime Corrosion Resistance
- ✓ Commercial / Industrial engines with high output charging systems

### Options...

Hose Reel (AR188), Hour meter (AM305), Wheel Kit options (AHA12, AHB12, or AHS12), Downstream soap injection kit (AC340), Antifreeze tank (WT0SW), Custom skid color (CTSKD), Mobile Wash Trailer, Tank Skid

| TO:             |  |
|-----------------|--|
| COMMENTS:       |  |
| YOUR PRICE:     |  |
| DISTRIBUTED BY: |  |



ETL Listed Certified to UL 1776 Certified to