

HYDRO TEK

CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374

phone 800.274.9376 or 1.909.799.9222

www.hydrotek.us fax 909.799.9888

T250

Trailer Series

ProTowWash® – Transport Trailer with 270 Gallon Tank

The T250 single axle trailer, with your choice of SS Mobile Wash Skid, is a fully integrated self-contained pressure washing system. The 270 Gallon water tank provides ample water to sustain many remote-cleaning requirements. The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum. Long life, rugged, durable and dependable service is engineered into the T250 Series Pro Tow Wash.

TECHNICAL DATA	T250E
MACHINE CAPACITY	To be ordered with an SS Series skid
SUSPENSION / AXLE	Single 3700# Torsion Axle-Up to 300% more wheel travel over conventional trailer
TRAILER BRAKES	Electric Brake, Breakaway Switch***
WHEEL / TIRE	2 - 14" Spoke Rim, 5 Lug / ST205/75D 14 Tires, 1760 Pounds capacity per tire
COUPLER / TONGUE	2" Ball Coupler, Dual Safety Chains
VEHICLE HITCH/GVWR	2" Ball Hitch, Class III 5000 Pound Rated, 21" to top of ball when trailer is attached 3500# GVWR – requires 2", class III ball on tow vehicle
FENDERS	12 GA steel fender with recessed tail light mount and license plate light
LIGHTS	Recessed Rubber Grommet Snap-In, DOT Approved
WIRING	7 way molded electrical connector
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter
WATER TANK	270 Gallon Capacity, Seamless Polyethylene, 10" lid, Garden Hose Fill Fitting
TANK DRAW/FILTER	1½" 80 Mesh Strainer with Drain, 1½" Fast Drain Valve
FRAME CONSTRUCTION	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish
WEIGHT / DIMENSIONS	608 Lbs. Empty (No Machine) 125" x 70" x 61"

*Specifications subject to change without notification and may vary due to ambient conditions.

Note: Shipped To Distributors Only – Not Available to Drop Ship – Assembly Required

*** Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery. Fenders and tires require installation if being shipped.

Featuring:

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated storage tube for spray wands and large (47"x22"x10") storage box at the back of trailer for hoses and other accessories.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitations & contamination

Options...

Hose Reels, Lunette eye hitch, Stainless advertising panels, Chrome wheel upgrade, Custom trailer color (CTRLR), Front Bucket Rack (ACR02), 3-way ball valve (AW006), Light Bar rack (HLB98), High water tank shutoff (VVF18), Low water shutdown (AW410)-installed, Sand hopper, 12v Chemical sprayer with 40g tank (AC440), Locking storage lid option (ATH50)



Pressure washer not included
Shown with optional Hose Reel

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

* **WARNING:** Trailer brakes and a breakaway switch are recommended and required on the road in most states if the trailer weight exceeds 1500 pounds gross. Check your states requirements.