

### ProTowWash® – Transport Trailer with 540 Gallon Tank

The T500 tandem axle trailer, with your choice of pressure washer, is a fully integrated self-contained pressure washing system. The two 270 Gallon water tanks with integrated baffling provide 540 Gallons of ample water to sustain many remote-cleaning requirements. The dual water tanks provide flexibility for operation and can be either plumbed together or maintained separate. The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum.

TECHNICAL DATA	T500EE	T500S
MACHINE CAPACITY	To be ordered with a hot water skid (up to 1100# total)	
SUSPENSION / AXLE	2) 3700# Torsion axles-up to 300% more wheel travel over conventional trailers	
TRAILER BRAKES	Electric Brakes, both axles, Breakaway Switch***	Surge Brake – Rear Axle
WHEEL / TIRE	4) 14" Spoke Rims, 5 Lug, ST205/75D/14 Tires, 1760# capacity per tire @ 35psi	
COUPLER / TONGUE	2 <sup>5</sup> / <sub>16</sub> " Ball Coupler, Dual 3/8" Safety Chains	
VEHICLE HITCH / GVWR	2 <sup>5</sup> / <sub>16</sub> " Ball Hitch, Class IV, 7500 Pound Rated 7000# GVWR – requires 2 <sup>5</sup> / <sub>16</sub> " , class IV ball on tow vehicle	
FENDERS	12 GA steel fender with recessed tail light mount and license plate light	
LIGHTS	Recessed Rubber Grommet Snap-In, DOT Approved	
WIRING	7 way molded electrical connector	4 way flat electrical connector
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter	
WATER TANK	540 Gal. total capacity (dual 270 gal) seamless polyethylene, 10" lid, garden hose fill fitting	
TANK DRAW / FILTER	1½" 80 Mesh Strainer with Drain, 1½" Fast Drain Valve	
CONSTRUCTION	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish	
WEIGHT / DIM	1163 Lbs. Empty (No Machine) 168"L x 70"W x 61"H	

Note: Specifications subject to change without notification and may vary due to ambient conditions.

\*\*\* Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery. Fenders and tires require installation if being shipped.

#### Featuring:

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated storage tube for spray wands and large (47"x22"x10") storage box at the back of trailer for hoses and other accessories.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitations & contamination

#### Options...

Hose Reels, Lunette eye hitch, Stainless advertising panels, Chrome wheel upgrade, Custom trailer color (CTRLR), Front Bucket Rack (ACR06), 3-way ball valve (AW006), High water tank shutoff (VVF18), Low water shutdown (AW410)-installed, Sand hopper, Light Bar rack (HLB98), Vacuum hose hooks (HHP28), Hydro Vacuum wastewater recovery (AZV), 12v Chemical sprayer with 40gal tank (AC440), Locking storage lid option (ATH50), Fender mount storage bin (TTARD)



Pressure washer not included  
 Shown with optional Hose Reels and light bar

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_

**WARNING:** Trailer brakes and a breakaway switch are recommended and required on the road in most states if the trailer weight exceeds 1500 pounds gross. Check your states requirements.