

CW35006E3-E4

CW Series – Pressure Washer

Cold (HOT*) Water: Electric Powered – Stationary or Portable

The **CW** Series is a unique washer with hot water inlet capabilities that saves you time and money. Pressure clean thoroughly using your existing hot-water supply, up to 165°F. The CW's versatile design allows it to be wall-mounted, stationary or portable depending on the cleaning task or application. The adjustable pressure wand and auto start/time delay shutdown features give the operator total control from the wand – no traveling back and forth to the unit to adjust the pressure or turn switches. The heavy-duty industrial components, stainless steel frame/cover, and a low rpm belt drive pump for long lasting performance.

PRESSURE		
	3500 psi	
FLOW CAPACITY	5.6 gpm	
POWER / ENGINE	15 hp	
VOLTS / PHASE / AMPS	E3 is dual rated for 208v or 230v - 3ph, 29amp	E4 is 460v – 3ph
CONTROLS / SWITCHES	Hour meter, lighted on/off switch, soap control	
PUMP	General Pump, triplex ceramic plunger	
POWER DRIVE	V-Belt drive with EZ Align™ pump rail	
PRESSURE CONTROL	Adjustable pressure unloader, 24v adjustable timer with 7 to 300 second control	
WATER SUPPLY	Pressure feed from garden hose	
WATER TEMPERATURE	Inlet water temperature up to 165°F from hot water source	
SOAP INJECTION	Downstream soap injection included	
PRESSURE HOSE	3/8" x 50' 4000psi wire braided hose	
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler	
NOZZLE	#8.5 x 15°, 25°, 40°	
FRAME CONSTRUCTION	Stainless steel frame and removable cover	
WHEELS	Optional wheel / handle kit	
DIMENSIONS (LxWxH)	29" x 21" x 15" (31" x 31" x 20" with wheels, plus handle height)	
NET WEIGHT	200#	

Specifications subject to change without notification and may vary due to ambient conditions.

* CW Series accepts water from hot water heater or other hot water source up to 165°F

Featuring:

- All Stainless Construction is corrosion resistant and sanitary, ideal for use in food processing or medical facilities
- ✓ **EZ Align**[™] pump rail system for simple belt adjustments
- ✓ Auto ON/Off with time delay shutdown saves time & effort

Options...

Wall mount brackets, sideways mount (ACW09), Wall mount hose reels (AR188), Wheel/handle kit (AHS15), Multi station outlets (ACW20), Wall mount remote options (AEN35 or AEN22)

TO: _____

COMMENTS:

YOUR PRICE: _____ DISTRIBUTED BY:



ETL Listed

Certified to UL 1776 Certified to CAN/CSA B140.11