

# HYDRO TEK

CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374  
 phone 800.274.9376 or 1.909.799.9222  
 www.hydrotek.us fax 909.799.9888

# SM40004HG

## SM Series – Portable Wash Skid

### Steam / Hot / Cold Water – Self Contained, Portable: Diesel Heated, Gas Engine, 12v Burner

The SM Series is a compact and portable wash skid. It is powered by a gas engine and ready for use wherever a water source is available, no electricity required. With a SpiraLast coil and 12v burner you will quickly and efficiently heat water to effectively blast away grease and grime. The SM Series includes airless tires to eliminate flats on a jobsite and is easy to maneuver with the integrated handles. Stainless panel, coil enclosure, and rain guard are rust resistant and keep your machine looking great for years. The SM Series is a value conscious choice in hot water pressure washers without sacrificing performance, features, and operator safety.

|                          |  |
|--------------------------|--|
| <b>PRESSURE</b>          | 4000psi  |
| <b>FLOW CAPACITY</b>     | 3.5gpm   |
| <b>OUTLET TEMP</b>       | Adjustable to 250°F (100°F rise)   |
| <b>POWER/ENGINE</b>      | 389cc Honda, GX390 – electric start, single cylinder   |
| <b>ENGINE FUEL/CAP</b>   | Unleaded / 6.4 qt fuel tank integrated into the engine   |
| <b>CONTROLS/SWITCHES</b> | Adjustable thermostat, lighted control switch  |
| <b>PUMP</b>              | General Pump   |
| <b>POWER DRIVE</b>       | Direct Drive   |
| <b>PRESSURE CONTROL</b>  | Unloader valve, Industrial fittings, Safety burst disc, Relief valve                               |
| <b>WATER SUPPLY</b>      | Pressure feed from garden hose   |
| <b>PRESSURE HOSE</b>     | 3/8" x 50', 4000psi  |
| <b>GUN/WAND</b>          | 48" molded insulator wand with quick coupler   |
| <b>SOAP INJECTION</b>    | Downstream soap injection option available   |
| <b>NOZZLE</b>            | Size 3.5 (15°, 40°), 3 (Steam)   |
| <b>BURNER COIL</b>       | Spiralast™ robotically fused 1/2"sch. 80 steel, cold rolled, compact, 4 spiral, ceramic insulation |
| <b>BURNER/POWER</b>      | Oil fired, 12V, 20amp fuse protected, auto ignition, inline fuel filter                            |
| <b>BURNER FUEL/CAP</b>   | Diesel fuel, kerosene, or fuel oil, 8 gallons – 300,000 Btu input                                  |
| <b>CONSTRUCTION</b>      | Rugged, square tube steel frame, stainless panel, coil wrap, and double-wall coil end caps         |
| <b>WHEELS</b>            | Airless 4) wheel kit is included   |
| <b>WEIGHT/DIMENSION</b>  | 323#, 36" l x 28" w x 37" h  |

Specifications subject to change without notification and may vary due to ambient conditions – Battery not included

#### Featuring:

- ✓ **Airless tires** to prevent flats when pushing through an area with nails and glass
- ✓ **Stainless Steel** panel, coil wrap, & rain guard for Lifetime Corrosion Resistance
- ✓ **Multiple safety features** protect the equipment and operator: high limit thermostat, pressure relief valve, safety burst disc, and thermal pump protection
- ✓ **Commercial Honda engine**

#### Options...

Hour meter (AM305), Downstream soap injection kit (AC340), Stainless steel frame upgrade (HSM22), Frame mount pivoting hose reel (AR425-requires jumper hose)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_



Shown with optional stainless frame