

2353 Almond Ave. Redlands, CA 92374 phone 800.274.9376 or 1.909.799.9222 www.hydrotek.us fax 909.799.9888

HP20005E8

HP Series - Pressure Steamer

Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The *HP Series* combines the cleaning power of high pressure and high water flow with the grease cutting effectiveness of hot water. Simply pull the trigger on the spray gun, and instantly the machine turns itself on and delivers high pressure cleaning power. The temperature can be adjusted to cold, hot, or steam for any cleaning application. The portable design and stainless steel construction offers years of trouble free service and cleaning performance anywhere electrical power is available.

PRESSURE	2000psi
FLOW CAPACITY	4.3gpm
OUTLET TEMP	Adjustable up to 250°F (150°F rise)
POWER / ENGINE	6.5hp
VOLTS/PHASE/AMPS	Dual rated for 208v or 230v – 1ph, 30amp
CONTROLS/SWITCHES	Lighted on/off and lighted burner switch, thermostat, hour meter
PUMP	Cat Pump, Oil Bath, Triplex Ceramic Plunger, Brass Head, Stainless Steel Valves
POWER DRIVE	V Belt drive
PRESSURE CONTROL	Adjustable pressure unloader and wand, safety relief valve, safety burst disc
WATER SUPPLY	3-1/2 gal. float tank
PRESSURE HOSE	3/8" x 50' 4000psi Rated
SOAP INJECTION	Inlet chemical injection, injects at full pressure
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler
NOZZLE	#5.5 (15°, 40°) #4.5 (25° Steam)
BURNER COIL	Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
BURNER / POWER	Oil Fired, Forced Draft, Automatic Ignition, Fuel Solenoid, Fuel Filter with Water Separator
BURNER FUEL / CAP	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gallon capacity- 372,400 Btu input
CONSTRUCTION	All Stainless: frame, panels, coil wrap, and double wall coil end caps
WHEELS	4) 13" tires installed
NET WEIGHT / DIM	470#, 46"x29"x39"

HP shown with hose reel

Featuring:

- ✓ Performance: High heating ability and high flow increases cleaning speed and power
- ✓ Portability: Compact design for versatility and maneuverability.
- ✓ Durability: All Stainless steel construction and panels for lifetime corrosion resistance
- ✓ **Efficient:** High output diesel burner system offers clean burning and continuous hot water.
- ✓ Convenient: E.T.S. Electronic Trigger Start, 60 second delay Auto Off avoids risk of pump overheating and expensive thermal damage. Also features adjustable pressure at the wand

Options...

Hose Reel (AR189), Wet Sandblaster, Downstream injection kit

TO:	
COMMENTS:	
YOUR PRICE: DISTRIBUTED BY	



©2011 Hydro Tek (rev 03/15 HP20005E8

^{*} Specifications subject to change without notification and may vary due to ambient conditions