

2353 Almond Ave. Redlands, CA 92374 phone 800.274.9376 or 1.909.799.9222 www.hydrotek.us fax 909.799.9888

HP35005E3 / E4

HP Series – Pressure Steamer

Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The *HP Series* combines the cleaning power of high pressure and high water flow with the grease cutting effectiveness of hot water. Simply pull the trigger on the spray gun, and instantly the machine turns itself on and delivers high pressure cleaning power. The temperature can be adjusted to cold, hot, or steam for any cleaning application. The portable design and stainless steel construction offers years of trouble free service and cleaning performance anywhere electrical power is available.

3500psi		
4.3gpm		
Adjustable up to 250°F (150°F rise)		
10 hp		
Dual rated for 208v or 230v - 3ph, 28amp	460v, 3ph, 12.5amp	
Lighted on/off and lighted burner switch, thermostat, hour meter		
Cat Pump, Oil Bath, Triplex Ceramic Plunger, Brass Head, Stainless Steel Valves		
V Belt drive		
Adjustable pressure unloader and wand, safety relief valve, safety burst disc		
3-1/2 gal. float tank		
3/8" x 50' 5800psi non-marking hose		
Inlet chemical injection, injects at full pressure		
48" molded insulator, adj. pressure wand with quick coupler		
#4.5 (15°, 40°) #4 (25° Steam)		
Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation		
Oil Fired, Forced Draft, Automatic Ignition, Fuel Solenoid, Fuel Filter with Water Separator		
Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gallon capacity- 372,400 Btu input		
All Stainless: frame, panels, coil wrap, and double wall coil end caps		
4) 13" tires installed		
470#, 46"x29"x39"	500#, 46"x29"x39"	
	Adjustable up to 2 Adjustable up to 2 10 Dual rated for 208v or 230v - 3ph, 28amp Lighted on/off and lighted burne Cat Pump, Oil Bath, Triplex Ceramic Plui V Beli Adjustable pressure unloader and war 3-1/2 gal. 3/8" x 50' 5800psi Inlet chemical injection 48" molded insulator, adj. pres #4.5 (15°, 40°) Spiralast™ robotically fused ½" sch. 80 stee Oil Fired, Forced Draft, Automatic Ignition, Fu Diesel fuel #1 or #2, Kerosene, Stove oil, JF All Stainless: frame, panels, coil w 4) 13" tire	

HP shown with hose reel

Featuring:

- ✓ Performance: High heating ability and high flow increases cleaning speed and power
- ✓ Portability: Compact design for versatility and maneuverability.
- ✓ Durability: All Stainless steel construction and panels for lifetime corrosion resistance
- ✓ **Efficient:** High output diesel burner system offers clean burning and continuous hot water.
- ✓ Convenient: E.T.S. Electronic Trigger Start, 60 second delay Auto Off avoids risk of pump overheating and expensive thermal damage. Also features adjustable pressure at the wand

Options...

Hose Reel (AR189), Wet Sandblaster, Downstream injection kit

TO:		
COMMENTS:		
YOUR PRICE: _		
DISTRIBUTED B	Y:	



©2011 Hydro Tek (rev03/15 HP35005E3-E4

^{*} Specifications subject to change without notification and may vary due to ambient conditions