

HYDRO TEK

CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374
 phone 800.274.9376 or 1.909.799.9222
 www.hydrotek.us fax 909.799.9888



SCX30005-MS

SCX Series – Mobile Wash Skid

Hot / Cold Water – Self Contained: Diesel Heated, Diesel Engine with 12v burner system

The **SCX Series** mobile wash skid is a diesel powered and diesel heated pressure washer designed for the extreme duty user. It has extra features and heavy-duty components to make it suitable for use in harsh and remote environments. The 12v heating system is dependable and efficient, quickly heating up to 250° for stubborn grease and grime. The extra-large frame allows for high capacity fuel tanks and easy access to all components. Panel-mounted indicator lights monitor your engine temperature and oil pressure conditions while double-wall steel engine mounting and a side-mounted muffler reduces vibration.

PRESSURE	3000 psi (200 bar)
FLOW CAPACITY	5 gpm (18 l/m)
OUTLET TEMP	Adjustable to 250°F (121°C) / 120°F (49°C) heat rise
POWER/ENGINE	599cc Kubota, 2 cylinder, water-cooled, low-vibration, key switch shut off, emergency stop button
ENGINE FUEL/CAP	Diesel #2, 36 gallon (136 liters) for burner and engine
CONTROLS/SWITCHES	Panel mounted adjustable thermostat, Lighted burner on/off switch, Hour meter
PUMP	General Pump, triplex ceramic plunger, brass head, Low RPM
POWER DRIVE	V-Belt drive with EZ Align™ pump rail, stainless belt guard
PRESSURE CONTROL	Total relief unloader, Safety burst disc, Pressure relief valve
WATER SUPPLY	8 gallon (30 liters) float tank with low water shutdown
PRESSURE HOSE	3/8" x 50' Steel Wire Braid Hose 250°F 4000psi Rated
GUN / WAND	48" molded insulator wand with multi-nozzle holder and quick coupler
NOZZLE	#5.5 (15°, 40°) and #4.5 steam
SOAP INJECTION	Optional downstream injection kit available
BURNER COIL	SpiraLast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
BURNER/POWER	Diesel fired, 12v PowerLight technology burner, Spin-on fuel filter
BURNER FUEL/CAP	Diesel #2, 36 gallon (136 liters) for burner and engine – 386,000 Btu input
CONSTRUCTION	Rugged, powder coated Pro-Tect-It™ frame, stainless panel including front extension panel, coil wrap, and double-wall coil end caps (stainless frame option available)
WHEELS	Optional wheel kit available
WEIGHT/DIM.	690 51"l x 32 1/2" w x 47" h

Specifications subject to change without notification and may vary due to ambient conditions – Battery not included



Featuring:

- ✓ **Rugged Pro-Tect-It frame** with built in lifting eyes and multiple hose reel mounting points can be truck or trailer mounted or pulled with the optional wheel kit
- ✓ **Extreme duty** features and components for extra duty industrial use
- ✓ **Mine Specifications model includes:** Front panel extension, 8 gallon float tank, oil drain/drip pan, components are operating well below maximum ratings for prolonged life. Also included are enhanced safety features like a GeniSys flame-out safety control system to automatically shut down the burner, battery isolator switch to shut off battery power and emergency stop button



Options...

Hose Reels (jumper hose needed), Stainless frame option (HSX15), Custom skid color (CTSKD), Wheel Kit 13" w/pull bar steering (AHB12), Winterizing tank (AWTW1), Downstream soap injection kit (AC340), Trailer, Tank Skid (If you would like to add a vacuum filtration system, use RZV10E1 and a generator.)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

Stainless front panel extension included

