

2353 Almond Ave. Redlands, CA 92374 phone 800.274.9376 or 1.909.799.9222 www.hydrotek.us fax 909.799.9888

SS30005VH

SS Series – Mobile Wash Skid

Steam / Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine, 12v Burner

The *SS Series* is a power washer that uses the 12-volt charging system on the engine to power the diesel-fired burner giving you continuous hot water. Its compact size allows passage through commercial doorways, and simple design makes it easy to run and maintain. The SS series is versatile, you select a mounting option: on a trailer, on a truck, on wheels or stationary. The SS Series has the output to perform heavy duty cleaning without needing any outside electrical power. Simply turn the key for high pressure, hot cleaning strength. An invaluable piece of equipment for property management companies, farmers, mechanics or anyone requiring a mobile cleaning solution for dirt, grease, and grime.

and grime.	
PRESSURE	3000 psi
FLOW CAPACITY	4.8 gpm
OUTLET TEMP	Adjustable to 250°F (120°F rise)
POWER/ENGINE	479cc Vanguard, twin cylinder, Electric key start
ENGINE FUEL/CAP	Unleaded, 8 gal
CONTROLS/SWITCHES	Adjustable thermostat, lighted control switch
PUMP	AR Pump, Triplex Ceramic Plunger
POWER DRIVE	V-Belt Drive with EZ Align™ pump rail, stainless belt guard
PRESSURE CONTROL	Unloader valve, Industrial fittings, Safety burst disc, Pressure relief valve
WATER SUPPLY	Pressure feed from garden hose with convenient frame mounted fitting, (float tank avail.)
PRESSURE HOSE	3/8" x 50', 3000psi
GUN/WAND	48" molded insulator wand with multi-nozzle holder and quick coupler
SOAP INJECTION	Optional soap injection available
NOZZLE	Size 5.5 (15°,40°) and 4.5 (25° steam)
BURNER COIL	Spiralast [™] robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
BURNER/POWER	Oil fired, 12V, 20amp fuse protected, auto ignition, in-line fuel filter, flow switch burner control
BURNER FUEL/CAP	Diesel fuel, kerosene, or fuel oil, 8 gallons – 388,000 Btu input
CONSTRUCTION	Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps
WHEELS	Optional wheel kit available
WEIGHT/DIMENSION	472#, 47½" l x 27.5" w x 40.25" h
Creationations subject to abore without notification and mousers due to embient conditions. Detters not included	

Specifications subject to change without notification and may vary due to ambient conditions – Battery not included *Featuring*:

- Rugged "Pro-Tec-It' Frame surrounds and protects vital pressure washer components
- ✓ Stainless Steel panels for Lifetime Corrosion Resistance
- ✓ EZ Align™: Hydro Tek's belt tensioning system makes belt adjustments easy, with a single bolt, and has an integrated selfaligning mono rail pump mount
- High Altitude Rated extra air band capacity available
- ✓ Low Pressure, Hot (160°+) water rinse

Options...

Hose Reel (AR188), Hour meter (AM305), Wheel Kit options (AHA12, AHB12, or AHS12), Downstream soap injection kit (AC340), Float tank with inlet injection (WT0SS), Antifreeze tank (WT0SW), Custom skid color (CTSKD), Mobile Wash Trailer, Tank Skid

ТО: ____

COMMENTS:

YOUR PRICE: _____ DISTRIBUTED BY:



©2012 Hydro Tek (rev03/15 SS30005VH)