

Cold (HOT*) Water: Electric Powered – Stationary or Portable

The **CW Series** is a unique washer with hot water inlet capabilities that saves you time and money. Pressure clean thoroughly using your existing hot-water supply* (up to 165°F standard or up to 190°F with available options). The CW's versatile design allows it to be wall-mounted, stationary or portable depending on the cleaning task or application. The adjustable pressure wand and auto start/time delay shutdown features give the operator total control from the wand – no traveling back and forth to the unit to adjust the pressure or turn switches. The heavy-duty industrial components, stainless steel frame/cover, and a low rpm belt drive pump for long lasting performance.

PRESSURE	1000 psi
FLOW CAPACITY	3.0 gpm
POWER / ENGINE	2.0 hp
VOLTS / PHASE / AMPS	115v / 1ph / 20amp
CONTROLS / SWITCHES	Hour meter, lighted on/off switch, soap control, GFCI & 35' cord included 24v adjustable timer with 7 to 300 second control
PUMP	General Pump, triplex ceramic plunger
POWER DRIVE	V-Belt drive with EZ Align™ pump rail
PRESSURE CONTROL	Adjustable pressure unloader, Safety relief valve
WATER SUPPLY	Pressure feed from garden hose
WATER TEMPERATURE	Inlet water temperature up to 165°F from hot water source, up to 190°F* with options
SOAP INJECTION	Downstream soap injection included, inlet soap injection option available
PRESSURE HOSE	3/8" x 50' 3000psi wire braided hose
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler
NOZZLE	#5.5 x 15°, 25°, 40°
FRAME CONSTRUCTION	Stainless steel frame and removable cover
WHEELS	Optional wheel / handle kit
DIMENSIONS (LxWxH)	29" x 21" x 15" (31" x 31" x 20" with wheels, plus handle height)
NET WEIGHT	140#

Specifications subject to change without notification and may vary due to ambient conditions.

* CW Series accepts water from hot water heater or other hot water source up to 165°F as equipped, or up to 190°F with an optional seal or pump upgrade



Featuring:

- ✓ **All Stainless Construction** is corrosion resistant and sanitary, ideal for use in food processing or medical facilities
- ✓ **EZ Align™** pump rail system for simple belt adjustments
- ✓ **Auto ON/Off** with time delay shutdown saves time & effort

Options...

185°F inlet temp rating option (-HT), Cat pump upgrade with 190°F inlet temp rating (-CAT), Wall mount brackets, sideways mount (ACW09), Wall mount hose reels (AR188), Wheel/handle kit (AHS15), Float tank/inlet soap injection option (WTOCW – not compatible with high temp options or 8gpm models), Multi station outlets (ACW20), Wall mount remote options (AEN35 or AEN22)



Shown with optional wheel / handle kit

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____