

CW30008E3-E4

CW Series - Pressure Washer

Cold (HOT*) Water: Electric Powered – Stationary or Portable

The **CW Series** is a unique washer with hot water inlet capabilities that saves you time and money. Pressure clean thoroughly using your existing hot-water supply, up to 165°F. The CW's versatile design allows it to be wall-mounted, stationary or portable depending on the cleaning task or application. The adjustable pressure wand and auto start/time delay shutdown features give the operator total control from the wand – no traveling back and forth to the unit to adjust the pressure or turn switches. The heavy-duty industrial components, stainless steel frame/cover, and a low rpm belt drive pump for long lasting performance.

| unive pump for long lasting pe | nomanee. | |
|--------------------------------|--|------------------|
| PRESSURE | 3000 psi | |
| FLOW CAPACITY | 7.4 gpm | |
| POWER / ENGINE | 15 hp | |
| VOLTS / PHASE / AMPS | E3 is dual rated for 208v or 230v - 3ph, 29amp | E4 is 460v – 3ph |
| CONTROLS / SWITCHES | Hour meter, lighted on/off switch, soap control, 24v adjustable timer with 7 to 300 second control | |
| PUMP | General Pump, triplex ceramic plunger | |
| POWER DRIVE | V-Belt drive with EZ Align™ pump rail | |
| PRESSURE CONTROL | Adjustable pressure unloader, Safety relief valve | |
| WATER SUPPLY | Pressure feed from garden hose | |
| WATER TEMPERATURE | Inlet water temperature up to 165°F from hot water source | |
| SOAP INJECTION | Downstream soap injection included | |
| PRESSURE HOSE | 3/8" x 50' 3000psi wire braided hose | |
| GUN / WAND | 48" molded insulator, adj. pressure wand with quick coupler | |
| NOZZLE | #8.5 x 15°, 25°, 40° | |
| FRAME CONSTRUCTION | Stainless steel frame and removable cover | |
| WHEELS | Optional wheel / handle kit | |
| DIMENSIONS (LxWxH) | 29" x 21" x 15" (31" x 31" x 20" with wheels, plus handle height) | |
| NET WEIGHT | 200# | |
| | | |

Specifications subject to change without notification and may vary due to ambient conditions.

* CW Series accepts water from hot water heater or other hot water source up to 165°F

Featuring:

- ✓ All Stainless Construction is corrosion resistant and sanitary, ideal for use in food processing or medical facilities
- ✓ **EZ Align**™ pump rail system for simple belt adjustments
- ✓ Auto ON/Off with time delay shutdown saves time & effort

Options...

Wall mount brackets, sideways mount (ACW09), Wall mount hose reels (AR188), Wheel/handle kit (AHS15), Multi station outlets (ACW20), Wall mount remote options (AEN35 or AEN22)

| TO: | |
|-----------------|--|
| COMMENTS: | |
| YOUR PRICE: | |
| DISTRIBUTED BY: | |



ETL Listed Certified to UL 1776

Certified to CAN/CSA B140.11