SC MOBILE WASH SKID SC SERIES: DIESEL HEATED, GAS OR DIESEL ENGINE









DESIGNED FOR THE NEEDS OF A CLEANING PROFESSIONAL

MOBILE WASH SKID SELF CONTAINED - HOT/COLD WATER: with on-board 2900w generator

Rugged "Pro-tect-it" Frame:

Hydro Tek's unique "Pro-tect-it" frame of 1¼", heavy gauge steel, with durable electrostatically applied powder coat finish. Tie down brackets / 4-point lifting eyes as well as hose reel mounting holes incorporated into the frame.

Stainless Steel Panels:

These rugged and durable panels offer lifetime corrosion resistance and protection of your valuable investment from the harshest environments. Keeps your machine looking like new for years to come.

SpiraLast™ Coil and Heating System:

A 110v oil fired burner is paired with the Hydro Tek manufactured SpiraLast[™] heating coil for an efficient heating system. Robotically fused ½" schedule 80 steel pipe is cold rolled to protect the steel pipe from fatigue and the spiral coil is then surrounded by ceramic insulation and stainless enclosure with double-wall end caps. Ask your dealer about the Lifetime Coil Warranty.

Industrial Engines:

Efficient OHV gas engines with electric key start, low oil shutdown, and cast iron cylinder for maximum duty and performance. Some models equipped with a durable, water-cooled diesel engine with key-switch shutdown, for enhanced longevity and single fuel source.

Fuel Tanks:

Heavy Duty "roto-molded" rust free fuel tanks with fuel filter to protect against contaminated fuel. Extended run time (up to 8hrs.) eliminates interruptions. High capacity 8 gallon gas and 18 gallon diesel fuel tank decrease refueling and operator down time.

Total Relief Unloader - Remote Mounted:

Flow sensitive unloader allows pressure to build up gradually as trigger gun is activated eliminating "pressure spikes" and improving operator control and safety. When the gun is released, entire system pressure is relieved, enhancing system life and eliminating engine starting problems. The unloader is panel mounted eliminating heat failure and vibration. Balanced regulating unloader on 2-gun systems.

NEMA4- Water Tight Control Panel:

ETL certified to UL1776 Class 2, for use in wash-down area, exceeding Industry standards. Special Hydro Tek control box features easy to use controls and provides instant access to electronics.

110v Diesel Fired Burner with On-Board 2900 watt Generator:

Provides automatic, high intensity ignition and reliable power for the heating system. Supplemental power from the generator offer the operator the option to run lights or accessories.

Belt Driven Pump:

V-belt driven pump, low RPM drive - cooler and quieter operation for continuous duty performance. EZ Align[™] belt tensioning system allows for easy, single bolt, belt adjustments.

More Standard Features:

- Burst disc technology for operator safety
- Adjustable thermostat
- Heavy duty gun and wand with insulated quick couplers, 3 or more nozzles, nozzle storage, 50' hose, snap top battery box
- Hour meters are included on diesel models

2 Gun Operation Capabilities:

(Refer to specifications chart on right for available models)

Unmatched Durability: The SC is a proven model manufactured and refined for over two decades.





Specifications									
Model	PSI	GPM	Temp.	CC	Engine				
SC30004VG	3000	4.0	250° F	479	Vanguard Gas				
SC30006VH	3000	5.5	250° F	570	Vanguard Gas				
SC30008HG*	3000	7.8	200° F	688	GX630 Honda Gas				
SC35005VH	3500	4.8	250° F	570	Vanguard Gas				
SC35005VG	3500	4.7	250° F	570	Vanguard Gas				
SC35005VC	3500	4.5	250° F	570	Vanguard Gas				
SC35006VG	3500	5.5	250° F	627	Vanguard Gas				
SC35006HG	3500	5.5	250° F	688	GX630 Honda Gas				
SC35008HAF**	3500	7.7/2	200° F	688	GX690 Honda Gas				
SC35008KAF**	3500	7.7/2	200° F	725	Kohler Gas				

Note: The diesel models below are still available and are manufactured in the 2014 frame and chassis design.

SC30008DAF**	3000	7.6/2	200° F	719	Kubota Diesel
SC35006DAF*	3500	5.5	200° F	599	Kubota Diesel

* Two gun system compatible

- **Includes two guns, wands, hoses
 - Specifications may vary, consult factory for custom models

Dimensions: 51"Lx34"Wx41"H without wheel kit

Optional Accessories:

Hour Meter, soap injection, stainless frame, custom skid color, Hydro Twister® concrete cleaner, wet sandblast, stainless hose reel, wheel kits, trailers & tank skid systems, 12v AGM sealed battery

Hydro Vacuum Wastewater Recovery: The SC Series generator will power the Hydro Vacuum AZV system to capture, filter and recycle used wash water, saving time, money and the environment.

HYDROTEK CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374 phone 800.274.9376 or 1.909.799.9222 www.hydrotek.us fax 909.799.9888 sc series 2/15 HYDRO TEK ©

DISTRIBUTED BY:

SC SERIES