

www.hydrotek.us fax 909.799.9888



## SCX Series - Mobile Wash Skid

## Hot / Cold Water - Self Contained: Diesel Heated, Diesel Engine with 12v burner system

The **SCX Series** mobile wash skid is a diesel powered and diesel heated pressure washer designed for the extreme duty user. It has extra features and heavy-duty components to make it suitable for use in harsh and remote environments. The 12v heating system is dependable and efficient, quickly heating up to 250° for stubborn grease and grime. The extra-large frame allows for high capacity fuel tanks and easy access to all components. Panel-mounted indicator lights monitor your engine temperature and oil pressure conditions while double-wall steel engine mounting and a side-mounted muffler reduces vibration.

PRESSURE	3000 psi (200 bar)	
FLOW CAPACITY	5.5 gpm (21 l/m)	
OUTLET TEMP	Adjustable to 250° F (121°C) / 100°F (38°C) heat rise	
POWER/ENGINE	599cc Kubota, 2 cylinder, water-cooled, low-vibration, key switch shut off,	
	emergency air choke shutdown	
ENGINE FUEL/CAP	Diesel #2, 36 gallon for burner and engine	
CONTROLS/SWITCHES	Panel mounted adjustable thermostat, Lighted burner on/off switch, Hour meter	
PUMP	General Pump, triplex ceramic plunger, brass head, Low RPM	
POWER DRIVE	V-Belt drive with EZ Align™ pump rail, stainless belt guard	
PRESSURE CONTROL	Pressure sensitive unloader, Safety burst disc, Pressure relief valve	
WATER SUPPLY	Feed with bulk water supply tank or garden hose (fittings required)	
PRESSURE HOSE	3/8" x 50' Steel Wire Braid Hose 250°F 3000psi Rated	
GUN / WAND	48" molded insulator wand with multi-nozzle holder and quick coupler	
NOZZLE	#6 (15°, 40°) and #4 steam	
SOAP INJECTION	Optional downstream injection kit available	
BURNER COIL	SpiraLast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation	
BURNER/POWER	Diesel fired, 12v PowerLight technology burner, Spin-on fuel filter	
BURNER FUEL/CAP	Diesel #2, 36 gallon for burner and engine – 405,000 Btu input	
CONSTRUCTION	Stainless steel Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps	
WHEELS	Optional wheel kit available	
WEIGHT/DIM.	680 51"l x 32½"w x 47"h	

Specifications subject to change without notification and may vary due to ambient conditions - Battery not included

## Featuring:

- ✓ **Burner is powered by a 12-volt** charging system for continuous hot water cleaning up to 250°F wet steam ideal for oilfield applications
- Rugged Pro-Tect-It frame with built in lifting eyes and multiple hose reel mounting points can be truck or trailer mounted or pulled with the optional wheel kit
- ✓ **Extreme duty** features and components for extra duty industrial use
- ✓ *Oil Specifications model includes:* Stainless steel frame, emergency air choke shutdown, stainless steel oil drain/drip pan

## Options...

Hose Reels (jumper hose needed), Stainless front extension panel (HSCX5), Custom skid color (CTSKD), Downstream soap injection kit (AC380), Wheel Kit 13" w/pull bar steering (AHB12), Winterizing tank (AWTW1), Trailer, Tank Skid (If you would like to add a vacuum filtration system, use RZV10E1 and a generator.)

TO:	
COMMENTS:	
YOUR PRICE:	
DISTRIBUTED BY:	



Included, but not shown in photo: stainless steel frame

ETL Listed tified to UL of Certified to

CAN/CSA B140.11