

# SS35004VG

## SS Series - Mobile Wash Skid

## Steam / Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine, 12v Burner

The **SS Series** is a power washer that uses the 12-volt charging system on the engine to power the diesel-fired burner giving you continuous hot water. Its compact size allows passage through commercial doorways, and simple design makes it easy to run and maintain. The SS series is versatile, you select a mounting option: on a trailer, on a truck, on wheels or stationary. The SS Series has the output to perform heavy duty cleaning without needing any outside electrical power. Simply turn the key for high pressure, hot cleaning strength. An invaluable piece of equipment for property management companies, farmers, mechanics or anyone requiring a mobile cleaning solution for dirt, grease, and grime.

PRESSURE	3500 psi	
FLOW CAPACITY	4 gpm	
OUTLET TEMP	Adjustable to 250°F (140°F rise)	
POWER/ENGINE	479cc Vanguard, twin cylinder, Electric key start	
ENGINE FUEL/CAP	Unleaded, 8 gal	
CONTROLS/SWITCHES	Adjustable thermostat, lighted control switch	
PUMP	General Pump, Triplex Ceramic Plunger	
POWER DRIVE	V-Belt Drive with EZ Align™ pump rail, stainless belt guard	
PRESSURE CONTROL	Unloader valve, Industrial fittings, Safety burst disc, Pressure relief valve	
WATER SUPPLY	Pressure feed from garden hose with convenient frame mounted fitting, (float tank avail.)	
PRESSURE HOSE	3/8" x 50', 4000psi	
GUN/WAND	48" molded insulator wand with multi-nozzle holder and quick coupler	
SOAP INJECTION	Optional soap injection available	
NOZZLE	Size 4.0 (15°,40°) and 3.5 (25° steam)	
BURNER COIL	Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation	
BURNER/POWER	Oil fired, 12V, 20amp fuse protected, auto ignition, in-line fuel filter, flow switch burner control	
BURNER FUEL/CAP	Diesel fuel, kerosene, or fuel oil, 8 gallons – 390,600 Btu input	
CONSTRUCTION	Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps	
WHEELS	Optional wheel kit available	
WEIGHT/DIMENSION	476#, 47½"   x 27.5" w x 40.25" h	

Specifications subject to change without notification and may vary due to ambient conditions - Battery not included

#### Featuring:

- Rugged "Pro-Tec-It" Frame surrounds and protects vital pressure washer components
- ✓ Stainless Steel panels for Lifetime Corrosion Resistance
- ✓ **EZ Align™:** Hydro Tek's belt tensioning system makes belt adjustments easy, with a single bolt, and has an integrated self-aligning mono rail pump mount
- √ High Altitude Rated extra air band capacity available
- ✓ Low Pressure, Hot (160°+) water rinse

### Options...

Hose Reel (AR188), Hour meter (AM305), Wheel Kit options (AHA12, AHB12, or AHS12), Downstream soap injection kit (AC340), Float tank with inlet injection (WT0SS), Antifreeze tank (WT0SW), Custom skid color (CTSKD), Mobile Wash Trailer, Tank Skid

TO:	
COMMENTS:	
YOUR PRICE:	
DISTRIBUTED BY:	



