

HE30005E4HE Series – All Electric

Cold / Hot / Steam Pressure Washer- All Electric Powered and Heated

The *HE Series* is an environmentally friendly, all electric hot water pressure washer. Safe for indoor operation, it does not require exhaust ducting or emit hazardous fumes into the workplace. The unique, maintenance free electric heating system provides high pressure hot water on demand. The highly efficient electric heating system uses 460V power, eliminating the need for combustible fuels.

PRESSURE	3000psi	
FLOW CAPACITY	4.8gpm	
OUTLET TEMP	Adjustable thermostat up to 250°F (110°F heat rise)	
POWER/ENGINE	10hp industrial motor	
VOLTS/PHASE/AMPS	460 Volts / 3 Phase / 12.6 Amps (92 total system Amps)	
CONTROLS/SWITCHES	Panel mounted hour meter, lighted on/off switches, adjustable thermostat, staged power distribution, auto start with adjustable time delay shutdown	
PUMP	General Pump, Triplex, oil-bath crank case, ceramic plungers with lubricated packings	
POWER DRIVE	V-Belt drive	
PRESSURE CONTROL	Pressure sensitive unloader, safety relief valve, safety burst disc	
WATER SUPPLY	Direct Feed, low water safety shutdown	
PRESSURE HOSE	3/8" x 50', 4000psi hose	
GUN/WAND	48" adjustable pressure, dual lance wand and quick coupler	
NOZZLE	Quick connect nozzles: #5.5 (15°, 40°) and steam	
SOAP INJECTION	Downstream soap injection included	
HEATING ELEMENT	1½" sch. 80 galvanized pipe	
BURNER/POWER	Electric, 460V, 60kW heating system (6 heating elements @ 10kW each)	
FRAME CONSTRUCTION	Rugged, powder-coated frame with lifting eyes and two-way forklift access, stainless panels and coil housing	
WEIGHT/DIMENSION	549# / 46"L x 25.5"W x 36.5"H	

^{*}Specifications subject to change without notification and may vary due to ambient conditions.

Featuring:

- ✓ Smart Start™ 3-Stage Startup eliminates full amp surge at startup, preventing circuit overload of the power source.
- ✓ No Emissions or Fumes. Ideal for indoor plant operation, food processing facilities, mines, or in areas where strict emissions control is mandatory.
- ✓ **Low Water Shutoff** when inlet water pressure is too low, under 20psi, machine will shut off to protect vital components.
- ✓ Instant Heat with a unique heating element that provides continuous hot water, less than 3 minutes to reach maximum temperature

Options...

Stainless hose reels (req. jumper hose), 10 micron inlet water filter kit (AHE05), Anti-scale water filter kit (AHE00), Remote (AEN61)

TO:	
COMMENTS:	
YOUR PRICE:	
DISTRIBUTED BY:	

