SPECIALTY ACCESSORIES



SUTTNER SLUDGE PUMP HOSE - HIGH OUTPUT

PART #	LGTH	FLOW RATE	INLET	ORIFICE	WT	LIST
999 001 540	15′	11:1	M22-M	#4.0 x 0°	7.5	\$245.51

NOTE: Attaches to any Pressure Washer & turns it into a High Output Pump. Great for Flood Cleanup, Car Wash Pits, Draining Pools, or Chemical Spills. Vacuums up Liquid Slurries at a Ratio of 11:1 (Example: 4 GPM will Produce 44 GPM Output) HOSE BARB: 1-1/2" / PSI: 4000 / TEMP: 104° F

MUCK SCUPPER SLUDGE & SLURRY EVACUATION TOOL



PART #	LGTH	INLET	ORIFICE	WT	LIST
ANS04	15′	1/4" QCP	#4.0	10.5	\$151.79
ANS55	15′	1/4" QCP	#5.5	10.5	\$151.79
DHB17	1-1/2"	Discharge Hos		\$5.19	

NOTE: Turn your pressure washer into a sludge, slurry, water evacuation tool. Pressure energy of spray from pressure washer wand creates suction that pulls water, up to 87gpm, through a 15' heavy wall 1½" discharge hose. Ideal for clean out of sump pots, draining a fountain or pond, and flood cleanup. Watch it in action at: www.hydrotek.us/accessories.htm



Connect to your existing 1/4" pressure washer wand quick connect coupler, no other tools required

	UNDERCARRIAGE WAND								
	PART #	PSI	GPM	LENGTH	INLET	OUTLET	WT	LIST	
HTC	AVUN1	5000	6	52"	1/4"QCS	1/4"QCS	7.5 \$	125.77	

For removing dirt and grime from underneath a vehicle, try Hydro Tek's undercarriage wand with casters. Simply attach the wand to your power washer gun, insert QC nozzle and roll under vehicle. The undercarriage wand is also ideal for cleaning under boat trailers and motor homes.





	UNDERCARRIAGE WASHER								
	MODEL	PSI	GPM	COVER	COVER DIAM.	WT	LIST		
ITCP	ANTUN	5000	6	SS	24"	27	\$1,218.38		

Clean the undercarriage of trucks, boats, and farm equipment. Attach this accessory to a hot or cold pressure washer to effortlessly remove grime from the underside of vehicles and equipment. If you need to clean concrete, simply reverse the casters and flip the deck over to be used as an efficient flat surface cleaner. Rust resistant, stainless steel construction, with an aluminum spray bar, to ensure a long life of use even in corrosive environments.

NOTE: 7" clearance height needed, 210°F Max.

HTCP HTCP