

HD30004E2G HD Series – Pressure Steamer

Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The *HD Series* offers rugged, dependable, affordable washing. It features a heavy-duty stainless steel frame, handles, panels and coil protection – offering superior corrosion resistance, as well as four pneumatic wheels. Panel mounted temperature control offers the benefits of high pressure cleaning with water temperature from cold through full Steam Settings. Panel mounted controls allow the operator to vary the mixture of soap, or other additives, which can be delivered at full pressure – for optimal cleaning effectiveness. High efficiency coil and large capacity diesel fuel tank offer up to 8 hours of operation between refueling. Ideal for farm and agricultural applications, auto repair shops, and wherever

sanitizing and degreasing are needed.

anitizing and degreasing are needed.		
PRESSURE	3000psi	
FLOW CAPACITY	3.9gpm	
OUTLET TEMP	Adj. to 250°F (130°F Rise)	
POWER/ENGINE	8.0 hp	
VOLTS/PHASE/AMPS	Dual rated for 208v or 230v – 1ph, 36amp	
CONTROLS/SWITCHES	Lighted rocker switches, panel mounted soap control, adjustable thermostat	
PUMP	General Pump, Triplex Ceramic Plunger w/ Oil Bath Crankcase	
POWER DRIVE	V-Belt Drive with EZ Align™ pump rail, Low RPM – Cooler, Quieter	
PRESSURE CONTROL	Adjustable Pressure Unloader, Safety Relief Valve, Burst Disc, By-Pass-Cool System	
WATER SUPPLY	4 Gal Float Tank, Double Inlet Filtration	
PRESSURE HOSE	3/8" x 50' Steel Wire Braid Hose, 3000 PSI, 250°F Rated	
GUN / WAND	Insulated Shut Off Gun / 36" Wand w/Nozzle Quick Connector	
SOAP INJECTION	Inlet soap/chemical injection, Injects soap at full pressure	
NOZZLE	#4.5 (15°,40°) #3.5(25°)	
BURNER COIL	Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation	
BURNER/POWER	Beckett Oil Fired, Automatic Ignition, Forced Draft, Fuel Filter w/ Water Separator	
BURNER FUEL / CAP	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gal. capacity – 351,000 Btu input	
CONSTRUCTION	All Stainless: frame, panels, coil wrap, and double wall coil end caps	
WHEELS	4) wheels installed	
NET WEIGHT / DIMS	393# 47x29x36	

^{*}Specifications subject to change without notification and may vary due to ambient conditions.

Featuring:

- Efficient Heating: Schedule 80 coil is stainless steel wrapped and insulated to make efficient use of the burner heat.
- ✓ Flexible, Effective Cleaning: Adjustable temperature with steam setting and soap/chemical injection delivers more cleaning power over a wide range of applications.
- ✓ Compact and Portable: Wheels included. Easily moved to wherever you need to clean

Options...

Stainless Steel Hose Reel (AR004), UL1776, CSA certification can be ordered with GFCI option (ACE00)

TO:	
COMMENTS:	
YOUR PRICE:	
DISTRIBUTED BY:	

